
Alternative Fuel Mecca

2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com

# 22GPM HIGH PRESSURE OIL TRANSFER PUMP

**SKU:** HO-2 4.2 10



**Price:** $1,799.00

Add to Cart

Good self-priming, so it is not necessary to pour lubricant before working.
■ High pressure, up to 1Mpa.
■ The max temperature is up to 300℃.
■ Electric motor or diesel engine driven.
■ No Bypass
**Categories:** Heavy Oil Pumps, Oil Transfer Pumps |

## SPECIFICATIONS

| | |
|---|---|
| **Weight** | 75 lbs |
| **Dimensions** | 24 × 16 × 14 in |

## PRODUCT DESCRIPTION

The **HO-2 4.2/10** is a compact, heavy-duty positive-displacement gear pump designed for transferring lubricating oils, fuel oils, hydraulic oils, and other clean, lubricating fluids where dependable flow and higher discharge pressure are required.
Unlike centrifugal pumps, the HO-2 uses a **positive-displacement gear design**, providing consistent flow while developing up to **1.0 MPa (145 PSI)** discharge pressure. Higher pressure available. This makes it particularly well suited for transferring heavier oils through longer hoses, piping systems, filtration equipment, and other applications where a conventional low-pressure transfer pump may struggle.
The pump is paired with a **4 HP Electric Farm Duty motor**, providing a rugged North American motor package designed for demanding operating environments.

## Key Specifications

| Specification | HO-2 2.1/10 |
|---|---|
| Pump Type | Positive-displacement external gear pump |

2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com

| Specification | HO-2 2.1/10 |
|---|---|
| Model | **HO-2 2.1/10** |
| Nominal Flow | **22 GPM** |
| Maximum Pressure | **1.0 MPa / 145 PSI** |
| Motor | **4 HP Electric Farm Duty** |
| Motor Speed | **1800 RPM class** |
| Voltage | **115/230/460 VAC** |
| Phase | **Single phase/3 Phase** |
| Enclosure | **TEFC – Totally Enclosed Fan Cooled** |
| Protection | **IP54** |
| Service Factor | **1.15** |
| Insulation | **Class F** |
| Mounting | **Rigid base** |

## Farm Duty Motor

The pump is powered by a **Farm Duty TEFC motor**, selected for its high starting torque and durability in demanding environments. Farm Duty series features a **1.15 service factor, Class F insulation, IP54 protection, manual overload protection, Vacuum Pressure Impregnation (VPI), an anti-rust-treated rotor, and an improved drive-end shaft seal to help protect the bearing from moisture and contaminants**. The 1 HP version uses a capacitor-start/induction-run design.

Farm Duty Motor specifications

## Built for Difficult Oil-Transfer Applications

The combination of **moderate flow and high pressure** makes this pump especially useful for transferring viscous fluids where high-volume pumps aren't necessarily the best solution. Its positive-displacement gear mechanism maintains flow against increasing system resistance and can develop substantially more pressure than typical utility oil-transfer pumps.

Typical applications include **lubricating oil transfer, engine and gear oils, hydraulic oil, fuel oil, machinery lubrication systems, oil filtration and circulation systems, tank-to-tank transfer, and long-hose oil delivery systems**.

For applications involving **very cold or extremely viscous oil**, flow and required horsepower will depend strongly on viscosity and temperature. The pump, motor, hose, relief protection, and suction plumbing should therefore be sized for the actual fluid conditions.

## RELATED PRODUCTS



**2.4 GPM Viscomat Gear Oil Transfer Pump**



**Super HD Heavy Oil Transfer Pump**



**Food Grade Stainless Oil Circulating Pump 2GPM**



**Portable Oil Transfer Pump Reversible Switch**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning

centrifuges are also important tools to re-use oil as fuel or lubricant.

**Contact Us:**
2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com