



## 2HP HEAVY OIL PORTABLE PUMP - 3 PHASE

SKU: gs25-2-1



Price: ~~\$1,379.00~~ \$1,310.05

Add to Cart

Categories: [Heavy Oil Pumps](#), [Oil Transfer Pumps](#) |

### SPECIFICATIONS

<b>Weight</b>	50 lbs
<b>Dimensions</b>	20 x 14 x 16 in
<b>Fluid</b>	Heavy Oils like Gear Oil
<b>Voltage</b>	230V, 460V, 3 Phase
<b>Speed</b>	12GPM

### PRODUCT DESCRIPTION

#### Additional Specs:

\*Dimensions: 17" long x 11" wide x 7" tall (43 cm x 28 cm x 18 cm)

\*Weight: 45lbs

\*Self Priming

\*Suction Height: 15ft

\*Push Lift Height: 90ft

\***Reversible** - Rewire or add a switch to allow dual directional flow!



- \*Viton Seals
- \*B100 compatible
- \*Temperature Rating of 350°F
- \*Duty Cycle: Continuous
- \*Priming: Self priming
- \*12gpm(45 liters/min): 1" NPT threaded ports, 1.25" hose barbs
- \*Pump needs oil to lubricate the gears. Will not work with water.

**Motor Specs**

- \*Commercial Duty
- \*Output: 2 HP
- \*Speed: 1725 RPM
- \*Volts: 230/460v
- \*Hertz: 60
- \*Shaft Size: 5/8"
- \*Shaft Woodruff Key: 5 mm width x 5 mm deep x 16 mm length
- \*Motor Base Mount: 4.5" Long x 6.56" Wide

**Pumphead Specs**

- \*Bolt Pattern: 7 mm holes on a 85 mm circle
- \*Shaft Size: 14 mm keyed shaft
- \*Shaft Woodruff Key: 5 mm width x 5 mm deep x 12 mm length
- \*Viton Seals
- \*Self Priming
- \*Cast Iron
- \*1" NPT Ports
- \*Stainless Steel 1.25" Hose Barbs Included (fits 1.25" hose kit)
- \*No Pressure Regulator

**Coupling Specs**

- \*Pump Coupling: 5/8"
- \*Motor Coupling: 14 mm
- \*Size: C
- \*Overall Length: 1 63/64"
- \*Hub Diameter: 1 23/64"
- \*Bore Depth: 1 3/4"
- \*Screw Size: 1/4"-20
- \*Spider Element: Buna-N 27/64"

**RELATED PRODUCTS**



**HD Portable Oil Transfer Pump - Massive Gears**



**25GPM Portable Oil Transfer Pump - Massive Gears**



**Gear Oil Pump - Pumphead Only**



**Food Grade Stainless Oil Circulating Pump 2GPM**



Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

**Contact Us:**

2121 Natomas Crossing STE 200-218

Sacramento, CA 95835

1-888-959-9311

[info@alternativefuelmecca.com](mailto:info@alternativefuelmecca.com)

