


HOT OIL PUMP

SKU: Hot-oil-4gpm



Price: \$749.00

[Add to Cart](#)

Variable Speed Gear Pump
 1-3 Gallons/minute
 Runs off a VFD
 Supply with 120/230/480V
 VFD not included
 Bypass Optional

Categories: [Diesel Pumps](#), [Light Oil Pumps](#), [Oil Transfer Pumps](#) |

SPECIFICATIONS

Weight	45 lbs
Dimensions	20 x 14 x 16 in

PRODUCT DESCRIPTION

Additional Specs:

- *Dimensions: 17" long x 11" wide x 7" tall (43 cm x 28 cm x 18 cm)
- *Weight: 45lbs
- *Self Priming
- *Suction Height: 15ft
- *Push Lift Height: 90ft
- *Reversible** - Rewire or add a switch to allow dual directional flow!
- *Viton Seals
- *B100 compatible
- *Temperature Rating of 395°F
- *Duty Cycle: Continuous
- *Priming: Self priming
- *4 Gallons/min: 3/4" NPT threaded ports
- *Pump needs oil/diesel/glycol to lubricate the gears. Will not work with water.

Motor Specs

- *Commercial Duty



- *Output: 3/4 HP
- *Speed: 1725 RPM
- *Volts: 120V
- *Hertz: 60
- *Shaft Size: 5/8"
- *Shaft Woodruff Key: 5 mm width x 5 mm deep x 16 mm length
- *Motor Base Mount: 4.5" Long x 6.56" Wide
- *ODP motor to ventilate extra heat.

Pumphead Specs

- *Bolt Pattern: 7 mm holes on a 85 mm circle
- *Shaft Size: 14 mm keyed shaft
- *Shaft Woodruff Key: 5 mm width x 5 mm deep x 12 mm length
- *Viton Seals
- *Self Priming
- *Cast Iron
- *3/4" NPT Ports
- *Pressure Regulator/Bypass Optional

RELATED PRODUCTS



**Portable Oil Transfer
Pump Reversible
Switch**



**HD Portable Oil
Transfer Pump -
Massive Gears**



**480V Oil Pump
25GPM**



**Portable Pumphead
Replacement Gasket**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

Contact Us:

2121 Natomas Crossing STE 200-218

Sacramento, CA 95835

1-888-959-9311

info@alternativefuelmecca.com

