




INDUSTRIAL 8GPM WITH BYPASS

SKU: gsi-10



Price: ~~\$1,475.00~~ \$1,401.25

Add to Cart

Categories: [Diesel Pumps](#), [Glycol Pumps](#), [Heavy Oil Pumps](#), [Light Oil Pumps](#), [Oil Transfer Pumps](#) |

SPECIFICATIONS

Weight	50 lbs
Dimensions	20 x 14 x 16 in
Fluid	Diesel or Light Oils, Heavy Oils like Gear Oil, Motor Oil
Speed	4-7GPM
Voltage	120V, 230V

PRODUCT DESCRIPTION

Introducing the 1.5HP Oil Transfer Pump equipped with a 43psi pressure relief feature, designed specifically for hose reel applications where flow interruption occurs before the pump can be switched off (though prompt shutdown is still necessary to prevent overheating).

Featuring a robust construction and powered by a formidable Baldor Motor, this Heavy Duty gear pump stands out for its efficiency and reliability.

Key Features:

- **Self-Priming:** Capable of a suction height of up to 15ft.
- **Pressure Relief:** Ensures safe operation by releasing excess pressure automatically.



- **Solid Cast Iron Construction:** Equipped with Carbon Steel Gears for durability and longevity.
- **High-Quality Motor:** The 1.5HP motor operates seamlessly on both 120V and 220V power sources.

Operating Principle:

Within the pump body, twin rotary gears function with one being active and the other passive. The active gear drives the passive gear during operation, creating vacuum/suction in a pre-chamber. As gear teeth engage and disengage, liquid fills the gear cavities and is propelled at high pressure from the chamber.

Safety Relief Valve:


Factory-set, the safety valve is designed to automatically open in response to excess pressure within the pump or output piping. Once triggered, the valve redirects pressure and oil back to the inlet chamber, facilitating recirculation through the pumphead.

Compatibility and Specifications:

- **Pumphead:** Offers a flow rate of 9-11gpm at 1200rpm and features a pressure relief of 0.33Mpa, with a 20mm shaft and 1" ports.
- **Additional Components:** Includes 8.5" x 10 Base and Coupling for easy installation.
- **Motor Options:** Available with a Baldor Premium Efficient or Explosion-Proof motor.

Safety Note: This pump is not suitable for use with corrosive liquids and is intended for oil-only applications.

RELATED PRODUCTS



**Stainless Steel
12GPM Oil Transfer
Pump**

**25GPM Industrial
Pumphead Only**

**24GPM 12V Oil
Transfer Pump**

**480V Oil Pump at
12GPM**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

Contact Us:

2121 Natomas Crossing STE 200-218

Sacramento, CA 95835

1-888-959-9311

info@alternativefuelmecca.com

