



STAINLESS FOOD GRADE PUMP 5GPM

SKU: ft5ss



Price: ~~\$1,150.00~~ \$1,092.50

Add to Cart

Stainless or Brass pumps

5 Gallon/minute

120/230/480V options

Food grade

290PSI Max

158°F Max

Categories: [Oil Transfer Pumps](#), [Stainless Pumps](#) |

SPECIFICATIONS

PRODUCT DESCRIPTION


Technical features and manufacturing characteristics

The rotary vane pump with brass or stainless steel body utilizes a stainless steel AISI 303 rotor, while the pumping chamber and the vanes are in carbon graphite. Inlet and outlet ports are 1/2" GAS or NPT threaded and the pump could be equipped with a built-in adjustable relief valve. The pump can be connected to coupling direct motor with a metallic clamp or to M71 and M80 UNELMEC frame motors with the Fluid-o-Tech® coupling and adapter set. Maximum operative temperature: 70 °C (158 F) Available upon request:

- Viton®/EPDM seals
- Built-in relief valve
- Flange mount
- California AB 1953 compliant brass



RELATED PRODUCTS



**Stainless Steel
25GPM Oil Transfer
Pump**

**Industrial Oil
Transfer Pump -
25GPM - Single Phase**

**Portable Pump Shaft
Seal**

**7.5HP VFD for 60GPM
Pump Indoor**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

Contact Us:

2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com

