



SUPER HD HEAVY OIL TRANSFER PUMP 1.5HP

SKU: gs12-1-1



Price: ~~\$1,285.00~~ \$1,195.00

Stationary Pump for Heavy Oil

1.5HP Motor

No handle, switch or cord.

Categories: [Heavy Oil Pumps](#), [Oil Transfer Pumps](#) |

SPECIFICATIONS

Weight	50 lbs
Dimensions	20 x 14 x 16 in
Fluid	Heavy Oils like Gear Oil, Motor Oil
Speed	12GPM
Voltage	120V, 230V



PRODUCT DESCRIPTION

Additional Specs:

*Dimensions: 17" long x 11" wide x 7" tall (43 cm x 28 cm x 18 cm)

*Weight: 45lbs

*Self Priming

*Suction Height: 15ft

*Push Lift Height: 90ft

***Reversible** - Rewire or add a switch to allow dual directional flow!

*Viton Seals

*B100 compatible

*Temperature Rating of 400°F

*Duty Cycle: Continuous

*Priming: Self priming

*12gpm(45 liters/min): 1" NPT threaded ports, 1.25" hose barbs

*Pump needs oil to lubricate the gears. Will not work with water.

Motor Specs

*Commercial Duty

*Output: 1.5 HP

*Speed: 1725 RPM

*Volts: 120 or 220 (comes prewired for 120)

*Amps: 12.2 @ 120 volts, 6.1 @ 220 volts

*Hertz: 60

*Shaft Size: 5/8"

*Shaft Woodruff Key: 5 mm width x 5 mm deep x 16 mm length

*Motor Base Mount: 4.5" Long x 6.56" Wide

Pumphead Specs

*Bolt Pattern: 7 mm holes on a 85 mm circle

*Shaft Size: 14 mm keyed shaft

*Shaft Woodruff Key: 5 mm width x 5 mm deep x 12 mm length

*Viton Seals

*Self Priming

*Cast Iron

*1" NPT Ports

*Stainless Steel 1.25" Hose Barbs Included (fits 1.25" hose kit)

*No Pressure Regulator

Coupling Specs

*Pump Coupling: 5/8"

*Motor Coupling: 14 mm

*Size: C

*Overall Length: 1 63/64"

*Hub Diameter: 1 23/64"

*Bore Depth: 1 3/4"

*Screw Size: 1/4"-20

*Spider Element: Buna-N 27/64"

RELATED PRODUCTS



24GPM 12V Oil Transfer Pump



HD Portable Oil Transfer Pump - Massive Gears



7.5HP VFD for 60GPM Pump Indoor



Industrial Oil Transfer Pump - 25GPM - 3 Phase

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

Contact Us:

2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com

