



SUPER HD HEAVY OIL TRANSFER PUMP 1.5HP

SKU: gs12-1-1



Price: ~~\$1,195.00~~ \$1,135.25

Add to Cart

Stationary Pump for Heavy Oil

1.5HP Motor

No handle, switch or cord.

Categories: [Heavy Oil Pumps](#), [Oil Transfer Pumps](#) |

SPECIFICATIONS

Weight	50 lbs
Dimensions	20 x 14 x 16 in
Fluid	Heavy Oils like Gear Oil, Motor Oil
Speed	12GPM
Voltage	120V, 230V

PRODUCT DESCRIPTION

Additional Specs:

*Dimensions: 17" long x 11" wide x 7" tall (43 cm x 28 cm x 18 cm)

*Weight: 45lbs

*Self Priming



- *Suction Height: 15ft
- *Push Lift Height: 90ft
- *Reversible** - Rewire or add a switch to allow dual directional flow!
- *Viton Seals
- *B100 compatible
- *Temperature Rating of 400°F
- *Duty Cycle: Continuous
- *Priming: Self priming
- *12gpm(45 liters/min): 1" NPT threaded ports, 1.25" hose barbs
- *Pump needs oil to lubricate the gears. Will not work with water.

Motor Specs

- *Commercial Duty
- *Output: 1.5 HP
- *Speed: 1725 RPM
- *Volts: 120 or 220 (comes prewired for 120)
- *Amps: 12.2 @ 120 volts, 6.1 @ 220 volts
- *Hertz: 60
- *Shaft Size: 5/8"
- *Shaft Woodruff Key: 5 mm width x 5 mm deep x 16 mm length
- *Motor Base Mount: 4.5" Long x 6.56" Wide

Pumphead Specs

- *Bolt Pattern: 7 mm holes on a 85 mm circle
- *Shaft Size: 14 mm keyed shaft
- *Shaft Woodruff Key: 5 mm width x 5 mm deep x 12 mm length
- *Viton Seals
- *Self Priming
- *Cast Iron
- *1" NPT Ports
- *Stainless Steel 1.25" Hose Barbs Included (fits 1.25" hose kit)
- *No Pressure Regulator

Coupling Specs

- *Pump Coupling: 5/8"
- *Motor Coupling: 14 mm
- *Size: C
- *Overall Length: 1 63/64"
- *Hub Diameter: 1 23/64"
- *Bore Depth: 1 3/4"
- *Screw Size: 1/4"-20
- *Spider Element: Buna-N 27/64"

RELATED PRODUCTS





**Food Grade Stainless
Oil Circulating Pump
2GPM**

**HD Portable Oil
Transfer Pump -
Massive Gears**



**24GPM 12V Oil
Transfer Pump**

**7.5HP VFD for 60GPM
Pump Outdoor**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

Contact Us:

2121 Natomas Crossing STE 200-218
Sacramento, CA 95835
1-888-959-9311
info@alternativefuelmecca.com

