





**PORTABLE HEAVY DUTY OIL PUMP - 25GPM**

**SKU:** gs12-1-2



**Price:** ~~\$1,299.00~~ \$1,250.00

Add to Cart

Stationary Pump for Heavy Oil  
1.5HP Motor  
No handle, switch or cord.  
**Categories:** [Heavy Oil Pumps](#), [Oil Transfer Pumps](#) |



**SPECIFICATIONS**

|            |                 |
|------------|-----------------|
| Weight     | 50 lbs          |
| Dimensions | 20 × 14 × 16 in |



|                |                                     |
|----------------|-------------------------------------|
| <b>Fluid</b>   | Heavy Oils like Gear Oil, Motor Oil |
| <b>Speed</b>   | 25GPM                               |
| <b>Voltage</b> | 120V, 230V                          |

## PRODUCT DESCRIPTION

### Additional Specs:

\*Dimensions: 17" long x 11" wide x 7" tall (43 cm x 28 cm x 18 cm)

\*Weight: 45lbs

\*Self Priming

\*Suction Height: 15ft

\*Push Lift Height: 90ft

**\*Reversible** - Rewire or add a switch to allow dual directional flow!

\*Viton Seals

\*B100 compatible

\*Temperature Rating of 400°F

\*Duty Cycle: Continuous

\*Priming: Self priming

\*12gpm(45 liters/min): 1" NPT threaded ports, 1.25" hose barbs

\*Pump needs oil to lubricate the gears. Will not work with water.

### Motor Specs

\*Farm Duty

\*On/Off Switch and cord included

\*Capacitor Start / Capacitor Run (1.5-2 HP) for Reduced Amperage and High Torque

\*Manual Overload

\*Output: 1.5 HP

\*Speed: 3450 RPM

\*Volts: 120 or 220 (comes prewired for 120)

\*Amps: 16.4 @ 120 volts, 8.2 @ 220 volts

\*Hertz: 60

\*Shaft Size: 5/8"

\*Shaft Woodruff Key: 5 mm width x 5 mm deep x 16 mm length

\*Motor Base Mount: 4.5" Long x 6.56" Wide

### Pumphead Specs

\*Bolt Pattern: 7 mm holes on a 85 mm circle

\*Shaft Size: 14 mm keyed shaft

\*Shaft Woodruff Key: 5 mm width x 5 mm deep x 12 mm length

\*Viton Seals

\*Self Priming

\*Cast Iron

\*1" NPT Ports

\*Stainless Steel 1.25" Hose Barbs Included (fits 1.25" hose kit)

\*No Pressure Regulator

### Coupling Specs

\*Pump Coupling: 5/8"

\*Motor Coupling: 14 mm

\*Oversized Lovejoy L075 couplings



## RELATED PRODUCTS



**Portable Pumphead  
Replacement Gasket**



**480V Oil Pump  
25GPM**



**HD Portable Oil  
Transfer Pump -  
Massive Gears**



**230V Oil Pump  
25GPM - 2HP**

Since 2009, we have been supplying portable and stationary pumps for moving all types of oil. Oil cleaning centrifuges are also important tools to re-use oil as fuel or lubricant.

### **Contact Us:**

2121 Natomas Crossing STE 200-218

Sacramento, CA 95835

1-888-959-9311

[info@alternativefuelmecca.com](mailto:info@alternativefuelmecca.com)

